

CLAY-BASED MATERIALS AS FIRE PROTECTION FOR TIMBER STRUCTURES

Johanna Liblik

PhD Candidate
Department of Civil Engineering and Architecture
Tallinn University of Technology, Estonia

May 6th, 2023
1. Schweizer Lehmhaus Symposium / 5. – 7. Mai 2023 in Chur

1


CONTENTS



Fire safety
Design of initially protected timber structures



Research on clay plaster as a fire protection system




Proposed design guidelines and equations
Fire part of Eurocode 5




Reference to other studies and clay boards
Full-scale fire tests

**TAL
TECH**

2




3




4

INITIAL PHASE: REACTION TO FIRE



What does it mean?

Euroclass	Contribution to fire
A1	Non Combustible
A2	Limited Combustible No Flashover
B	No Flashover
C	Flashover after 10 minutes
D	Flashover before 10 minutes
E	Flashover before 2 minutes
F	No Performance Determined





TAL
TECH




Photos: WarringtonFireGent

5


FULLY DEVELOPED PHASE: FIRE RESISTANCE



Load bearing
(R)



Integrity
(E)




Insulation
(I)

Compartmentation (EI)

Images: träguiden.se

TAL
TECH



6

CLAY AND LIME PLASTER AS FIRE PROTECTION FOR STRAW BALE BUILDINGS

Fire protection of multi-storey straw bale buildings (2013) Wachtling, J., Hosser, D. & Zehfuß, J. Research and Applications in Structural Engineering, Mechanics and Computation – Zingoni (Ed.). Taylor and Francis Group, London.

- Furnace tests at TU Braunschweig, Germany
- Encapsulation of K₂60 could be achieved with clay board and clay plaster
- The fire resistance of plaster could be improved by certain additives

TAL
TECH



9



RESEARCH ON CLAY PLASTER AS FIRE PROTECTION FOR TIMBER


IN VIEW OF
FIRE PART OF EUROCODE 5

10

TEST MATERIALS

Plaster system

Plaster layer or sequence of plaster layers to be applied to a substrate, including the possible use of a carrier and/or reinforcement



Clay plasters:

different fibres (straw, cattail, hemp), grain sizes, products
density class 1.8 according to DIN 18947
thickness: 10 – 44 mm

**TAL
TECH**

11

SELECTION OF PLASTER SYSTEMS FOR TIMBER STRUCTURES

PLASTER CARRIER: REED MAT



PLASTER SUBSTRATE: REED BOARD 50 mm



**TAL
TECH**

12

EXPERIMENTAL WORK TEST METHODS

SMALL SCALE TESTS



**TAL
TECH**


INTERMEDIATE SCALE FURNACE TESTS



13

SMALL-SCALE TESTS

- Cone heater of the Cone Calorimeter ISO 5660
- Heat flux values: 50 and 75 kW/m²
- Test duration: 40 - 60 minutes
- Temperature measurements recorded by thermocouples behind plaster




**TAL
TECH**

14

SMALL-SCALE TESTS RESULTS

- Assessment of the heat transfer through the specimen



15


EXPERIMENTAL WORK FURNACE TESTS

Two main different set-ups of test specimens:

1 – Plaster system applied directly on timber

2 – Plaster system applied on reed board

- Standard fire exposure conditions
- 3 different furnaces, max size 1.5 m³
- 11 furnace tests
- Plaster system thicknesses 10 – 44 mm
- Selected types of plasters (DIN 18947)




TAL
TECH

16

EXPERIMENTAL WORK FURNACE TEST


- Test orientation: **Vertical**
- Fire exposed area: **950 mm x 950 mm**




- Performance of clay plaster system:
 - visible crack development in time
 - detachment of thick plaster layers

**TAL
TECH**

44 mm **clay plaster system with reed mat** on timber element



28 minutes (First crack) 60 minutes (Before layer detachment) 75 minutes (Before the end of test)



17

EXPERIMENTAL WORK FURNACE TEST

- Test orientation: **Horizontal**
- Fire exposed area: **600 mm x 950 mm**




**TAL
TECH**

17 mm **clay plaster system with reed mat** on timber element



First crack 19 min Largest cracks 31 min Before fall-off 75 min



18

EXPERIMENTAL WORK FURNACE TEST

- Test orientation: **Horizontal**
- Fire exposed area: **600 mm x 950 mm**




17 mm **clay plaster system on reed board** on timber element



Failure of plaster 17 mm. (no cracks before the fall off)

Reed board after failure of plaster

Before the end of test 44 min



Start time
of charring
of timber


**TAL
TECH**

LEHM 2020 – International Conference on Building with Earth

19

EXPERIMENTAL WORK FAILURE MODES OF CLAY PLASTER SYSTEMS

- 1) Failure of the mechanical fastening system
- 2) Loss of adhesion between the plaster and substrate



**TAL
TECH**

20

FURNACE TESTS CHARRING PERFORMANCE OF TIMBER STRUCTURES



**TAL
TECH**

21

SMALL SCALE METHOD FOR ESTIMATION OF FIRE PROTECTION EFFECT

▪ Cone heater test:

Test specimen: Plaster + Timber

- Plaster thickness 10 – 40 mm

- Timber specimen 100 x 100 x 100 mm

Test duration 40 min (50 and 75 kW/m²)



▪ Estimation of design parameters:

t_{ch} – start time of charring

k_2 – protection factor for the protected charring phase
(with modification factor)

LIMITATIONS: No failure time

**TAL
TECH**



22



DESIGN MODEL FOR CLAY PLASTER SYSTEMS DESIGN VALUES IN VIEW OF FIRE PART OF EUROCODE 5

23

DESIGN EQUATIONS FOR CLAY PLASTER SYSTEMS

- Plaster system directly applied on timber structures **IN WALLS**

$$h_p = 10 - 40 \text{ mm}$$



Plaster system with plaster carrier:

$$t_{f,pr} = t_{ch} + \frac{l_f - 10}{\beta_{n,Phase2}}$$

$$\beta_{n,Phase2} = k_2 \beta_0$$

$$k_2 = 1 - 0.01 \cdot h_p$$

$$\beta_0 = 0.65 \text{ mm/min}$$

Plaster system without plaster carrier:

$$t_{f,pr} = t_{ch}$$

$$t_{ch} = t_{prot,0,i} = 1.1h_p - 5.9$$



$$\beta_{n,Phase3} = k_3 \beta_0 = 2 \cdot \beta_0 = 1.3 \text{ mm/min}$$

24

DESIGN EQUATIONS FOR CLAY PLASTER SYSTEM

- Plaster system directly applied on timber structures with plaster carrier IN CEILINGS

$$h_p = 15 - 20 \text{ mm}$$




$$t_{ch} = t_{f,pr} = t_{prot,0,i} = 1.1h_p - 5.9$$

TAL
TECH

25

SEPARATING FUNCTION METHOD EI CRITERIA




TAL
TECH



prEN 1995-1-2:2022

26

DESIGN VALUES IN RESPECT TO THE REVISED EUROCODE 5 PART 1-2 SEPARATING FUNCTION METHOD



**TAL
TECH**

CLAY PLASTER AS FIRE PROTECTION MATERIAL:

$$t_{prot,i,0} = 1.1h_p - 5.9 = t_{ch}$$

$$t_{ins,0,n} = 0.6h_p - 3.9$$

Position coefficients according to Table 5.2 and 5.3 in FSITB.

FSITB: B. Östman, E. Mikkola, R. Stein, A. Frangi, J. König, D. Dhima, T. Hakkarainen and J. Bregulla, "Fire safety in timber buildings," Stockholm: SP Technical Research Institute of Sweden, 2010.

27

FULL-SCALE TEST CLAY PLASTER + PLYWOOD ON TIMBER FRAME ASSEMBLY



TAMPERE UNIVERSITY – FINLAND

Test time: 71 minutes

-> No failure of the plaster system

-> No EI performance failure




Plaster system collapsed when extinguishing the test specimen

**TAL
TECH**

28

STRAW BALE STRUCTURES WITH CLAY

- Tests in Europe, USA, Australia
- REI60, REI90, REI120



**TAL
TECH**

Test with clay board and plaster on chipboard (K₂60)
Judith Küppers, TU Braunschweig, Germany



Test was halted at 135 minutes with no failure of the test criteria
Report: Chilt/RF13217/AR1 A fire resistance test performed on a loadbearing compressed straw wall system


29

FULL-SCALE TESTS WITH CLAY BOARDS AND PLASTER AS FIRE PROTECTION

Available full-scale test reports

- Clay boards
- Clay board + plaster
- Clay plaster


PROPOSED DESIGN EQUATIONS
APPLY ALSO FOR CLAY BOARDS



**TAL
TECH**

30

CASE STUDY IN FINLAND FISKARS VILLAGE



TAL
TECH

31

CONCLUSIONS

- **Composition of plaster:**
 - Tested plasters demonstrated similar performance
 - Additives may increase fire resistance
- **Plaster thickness:**
 - Most significant factor influencing the charring of timber
 - Detachment of thicker plaster layers
- **Application of plaster onto timber structures:**
 - Plaster carrier and fastening to timber
 - Plaster without plaster carrier
- **FUTURE OUTLOOK:**
 - Different clay boards and combinations with plaster
 - Product development to improve fire protection ability



TAL
TECH

32

